



T Onyx 120C ep79 HA84



T Onyx 140R ep79 MHA84



T Onyx 2212C epa83 HP88

EPOXY (ep../epa..) - \square 40x40 mm - HT75 - incl. regelschroef - vis de réglage - Stellschraube - adjusting screw

Onyx HPL / HA / HM / MEL / MHA

		120C	100	110	120	120D	140R	120V	120VD	2212C	2412E	189	210
L x B		circ. 120x120	Ø100	Ø110	Ø120	Ø120+42,5x120	Ø140	120x120	120+40x120	Danish oval 220x120	ellipse 240x120	180x90	200x100
H (hpl)	HT75	76,0	76,0	76,0	76,0	75,8	75,2	75,8	75,2	75,8	75,8	75,8	75,8
BD (mm)	HPL/HA	26 mm	26 mm	26 mm	26 mm	24 mm	-	24 mm	-	24 mm	24 mm	24 mm	24 mm
	HM MEL/MHA	- -	18 mm -	- -	- -	- -	18 mm	- -	18 mm	- -	- -	18 mm	18 mm
PH PB PL	HT75	73,4	73,4	73,4	73,4	72,6	73,4	73,4	73,4	72,0	73,4	73,4	73,4
		-	-	-	-	-	-	-	-	-	-	-	-
		-	-	-	-	-	-	-	-	99,0	99,0	99,0	99,0
m^3 (ht75)		0,19	0,15	0,17	0,19	0,19	0,24	0,19	0,19	0,31	0,32	0,21	0,25
kg (ht75)	HPL/HA	31,8-36,3	23,8-27,4	26,6-30,5	29,4-33,9	47,3-52,1	-	32,5-37,0	-	53,9-62,6	53,4-61,2	39,3-44,9	45,3-51,3
	HM	-	23,7-27,3	-	-	-	-	-	-	-	-	39,2-44,8	45,2-51,2
	MEL/MHA	-	-	-	-	-	29,8-36,1	-	44,2-49,0	-	-	-	-

